GK-7

APPAREIL DE CONTROL DE L'IMPERMEABILITE
HYDROSTATIC HEAD TESTER

L'appareil à tête hydrostatique détermine avec précision et rapidité la perméabilité à l'eau des tissus. Cet appareil est surtout conçu pour les tissus épais (toile, toile goudronnée, bâche, etc...). La tête hydrostatique qui recouvre le tissu permet d'estimer la perméabilité du tissu. L'échantillon de tissu est
Soumis à une pression constante d'eau à vitesse stable jusqu'à ce que 3 gouttes d'eau pénètrent le tissu.
On enregistre la pression de l'eau du troisième lieu de pénétration de l'eau. La surface de l'échantillon est de 100 cm². On peut commander différentes tailles l'échantillon selon les différentes normes.
Le modèle électronique et manuel de l'appareil est disponible.

The hydrostatic head tester accurately and swiftly determines the water permeability of fabrics. This device is designed for thick fabrics (canvas, tarred canvas, tarp, etc...). The hydrostatic head is covered with the fabric to estimate the permeability of the fabric. The fabric sample is constantly pressurized with water at a stable speed until 3 drops of water penetration is realized. The pressure of the third penetrated place is recorded.
Sample area is 100 cm ².According to different standards in different sizes sample can be

---

NORMES & STANDARDS
BS EN 20811/3321/3424, AATCC 127, ISO 811, EN 1734, DIN 53886, NF 607-057, ERT 120,2-02

info@gateslab.com